

Section 1. Identification

Product name : QUICK HOLD
Product code : 1070105QH

Relevant identified uses of the substance or mixture and uses advised against

| Identified uses |
|-----------------|
| Adhesive. |

Supplier's details : Eclectic Products LLC
1075 Arrowsmith
Eugene, OR 97402
541-484-9621

Responsible name : Regulatory Affairs

Emergency telephone number (with hours of operation) : INFOTRAC
1-800-535-5053
001-352-323-3500
24 hours per day, 7 days per week.

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 - Highly flammable liquid and vapor.
H319 - Causes serious eye irritation.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.

Precautionary statements

Section 2. Hazards identification

- Prevention** :
- P280 - Wear protective gloves. Wear eye or face protection.
 - P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
 - P242 - Use only non-sparking tools.
 - P243 - Take precautionary measures against static discharge.
 - P233 - Keep container tightly closed.
 - P271 - Use only outdoors or in a well-ventilated area.
 - P261 - Avoid breathing vapor.
 - P264 - Wash hands thoroughly after handling.
 - P272 (OSHA) - Contaminated work clothing must not be allowed out of the workplace.
- Response** :
- P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
 - P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 - P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.
 - P333 + P313 - If skin irritation or rash occurs: Get medical attention.
 - P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P337 + P313 - If eye irritation persists: Get medical attention.
- Storage** :
- P405 - Store locked up.
 - P403 - Store in a well-ventilated place.
 - P235 - Keep cool.
- Disposal** :
- P103 - Read label before use.
 - P102 - Keep out of reach of children.
 - P101 - If medical advice is needed, have product container or label at hand.
- Hazards not otherwise classified** :
- None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

| Ingredient name | % | CAS number |
|--|-----------|------------|
| butanone | ≥25 - ≤50 | 78-93-3 |
| acetone | ≥10 - ≤25 | 67-64-1 |
| 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate | ≤0.3 | 57583-35-4 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** :
- Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Section 4. First aid measures

- Inhalation** : Remove person to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove person to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.

- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-----------------|--|
| butanone | <p>ACGIH TLV (United States, 3/2017). Notes: Substances for which there is a Biological Exposure Index or Indices</p> <p>STEL: 885 mg/m³ 15 minutes. STEL: 300 ppm 15 minutes. TWA: 590 mg/m³ 8 hours. TWA: 200 ppm 8 hours.</p> <p>NIOSH REL (United States, 10/2016).</p> <p>STEL: 885 mg/m³ 15 minutes. STEL: 300 ppm 15 minutes. TWA: 590 mg/m³ 10 hours. TWA: 200 ppm 10 hours.</p> <p>OSHA PEL (United States, 6/2016).</p> |

Section 8. Exposure controls/personal protection

acetone

2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate

TWA: 590 mg/m³ 8 hours.
 TWA: 200 ppm 8 hours.
OSHA PEL 1989 (United States, 3/1989).
 STEL: 885 mg/m³ 15 minutes.
 STEL: 300 ppm 15 minutes.
 TWA: 590 mg/m³ 8 hours.
 TWA: 200 ppm 8 hours.

ACGIH TLV (United States, 3/2017).

STEL: 500 ppm 15 minutes.
 TWA: 250 ppm 8 hours.

NIOSH REL (United States, 10/2016).

TWA: 590 mg/m³ 10 hours.
 TWA: 250 ppm 10 hours.

OSHA PEL (United States, 6/2016).

TWA: 2400 mg/m³ 8 hours.
 TWA: 1000 ppm 8 hours.

OSHA PEL 1989 (United States, 3/1989).

Notes: The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors.

STEL: 2400 mg/m³ 15 minutes.
 STEL: 1000 ppm 15 minutes.
 TWA: 1800 mg/m³ 8 hours.
 TWA: 750 ppm 8 hours.

ACGIH TLV (United States, 3/2017).

Absorbed through skin.

TWA: 0.1 mg/m³, (as Sn) 8 hours.
 STEL: 0.2 mg/m³, (as Sn) 15 minutes.

NIOSH REL (United States, 10/2016).

Absorbed through skin.

TWA: 0.1 mg/m³, (as Sn) 10 hours.

OSHA PEL (United States, 6/2016).

TWA: 0.1 mg/m³, (as Sn) 8 hours.

OSHA PEL 1989 (United States, 3/1989).

Absorbed through skin.

TWA: 0.1 mg/m³, (measured as Sn) 8 hours.
 Form: Organic

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Clear.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 3.79
- Melting point** : Not available.
- Boiling point** : >100°C (>212°F)
- Flash point** : Closed cup: -5.55556°C (22°F) [D93]
Open cup: 2.77778°C (37°F) [D1310]
- Evaporation rate** : >1 (Water = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : 24.5 kPa (184 mm Hg) [room temperature]
- Vapor density** : >1 [Air = 1]
- Relative density** : 0.95
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): 36.733 cm²/s (3673.3 cSt)
- Flow time (ISO 2431)** : Not available.

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
- Incompatible materials** : Reactive or incompatible with the following materials:
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-------------|--------------------|------------|----------|
| butanone | LD50 Dermal | Rabbit | 6480 mg/kg | - |
| | LD50 Oral | Rat | 2737 mg/kg | - |
| acetone | LD50 Oral | Rat | 5800 mg/kg | - |
| 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate | LD50 Oral | Rat - Male, Female | 1150 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|--------------------------|-------------|
| butanone | Skin - Mild irritant | Rabbit | - | 24 hours 14 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |
| acetone | Eyes - Mild irritant | Human | - | 186300 parts per million | - |
| | Eyes - Mild irritant | Rabbit | - | 10 microliters | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 20 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 395 milligrams | - |

Sensitization

Section 11. Toxicological information

| Product/ingredient name | Route of exposure | Species | Result |
|--|-------------------|------------|-------------|
| 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate | skin | Guinea pig | Sensitizing |

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Development toxin | Species | Dose | Exposure |
|--|-------------------|-----------|-------------------|---------|----------------|----------|
| 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate | Positive | - | - | Rat | Oral: 10 mg/kg | - |

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|----------|------------|-------------------|------------------|
| butanone | Category 3 | Not applicable. | Narcotic effects |
| acetone | Category 3 | Not applicable. | Narcotic effects |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Section 11. Toxicological information

- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-------|--------------|
| Oral | 6308.5 mg/kg |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|----------------------------------|----------|
| butanone | Acute EC50 >500000 µg/l Marine water | Algae - Skeletonema costatum | 96 hours |
| | Acute EC50 5091000 µg/l Fresh water | Daphnia - Daphnia magna - Larvae | 48 hours |
| acetone | Acute LC50 3220000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute EC50 20.565 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute LC50 6000000 µg/l Fresh water | Crustaceans - Gammarus pulex | 48 hours |
| | Acute LC50 10000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 5600 ppm Fresh water | Fish - Poecilia reticulata | 96 hours |
| | Chronic NOEC 4.95 mg/l Marine water | Algae - Ulva pertusa | 96 hours |

Section 12. Ecological information

| | | | |
|--|-------------------------------------|--|---------|
| | Chronic NOEC 0.016 ml/L Fresh water | Crustaceans - Daphniidae | 21 days |
| | Chronic NOEC 0.1 ml/L Fresh water | Daphnia - Daphnia magna - Neonate | 21 days |
| | Chronic NOEC 5 µg/l Marine water | Fish - Gasterosteus aculeatus - Larvae | 42 days |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| butanone | 0.3 | - | low |
| acetone | -0.23 | - | low |

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.










United States - RCRA Toxic hazardous waste "U" List

| Ingredient | CAS # | Status | Reference number |
|---|-------|--------|------------------|
| Methyl ethyl ketone (MEK) (I,T); 2-Butanone (I,T) | - | Listed | U159 |
| Acetone (I); 2-Propanone (I) | - | Listed | U002 |

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | ADR/RID | IMDG | IATA |
|--------------------------------|--------------------|--------------------|-----------------------|-----------|-----------|-----------|
| UN number | 1133 | 1133 | 1133 | 1133 | 1133 | 1133 |
| UN proper shipping name | ADHESIVES | ADHESIVES | ADHESIVES | ADHESIVES | ADHESIVES | ADHESIVES |
| | | | | | | |

Section 14. Transport information

| | | | | | | |
|-----------------------------------|--|---|--|---|---|--|
| Transport hazard class(es) | 3  | 3   | 3  | 3   | 3   | 3  |
| Packing group | II | II | II | II | II | II |
| Environmental hazards | No. | Yes. | Yes. The environmentally hazardous substance mark is not required. | Yes. | Yes. | Yes. The environmentally hazardous substance mark is not required. |

Additional information

DOT Classification

- : **Reportable quantity** 11524.4 lbs / 5232.1 kg [1454.9 gal / 5507.5 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
- Limited quantity** Yes.
- Special provisions** 383
- Remarks** Limited quantity : < 0 . 3 gal

TDG Classification

- : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.
- Explosive Limit and Limited Quantity Index** 5
- Passenger Carrying Road or Rail Index** 5

ADR/RID

- : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Special provisions** 640 (C)
- Tunnel code** (D/E)

IMDG

- : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Emergency schedules** F-E, S-D
- Remarks** Limited quantity

IATA

- : The environmentally hazardous substance mark may appear if required by other transportation regulations.
- Remarks** Eligible to be shipped ID8000 until 2020. See applicable regulations.

Special precautions for user

- : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

- : Not available.

Section 15. Regulatory information

U.S. Federal regulations : TSCA 4(a) final test rules: acetaldehyde
 TSCA 8(a) PAIR: acetaldehyde
 Clean Water Act (CWA) 307: vinyl chloride

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard
 Immediate (acute) health hazard

Composition/information on ingredients

| Name | % | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|--|-----------|-------------|----------------------------|----------|---------------------------------|---------------------------------|
| butanone | ≥25 - ≤50 | Yes. | No. | No. | Yes. | No. |
| acetone | ≥10 - ≤25 | Yes. | No. | No. | Yes. | No. |
| 2-ethylhexyl 10-ethyl-4, 4-dimethyl-7-oxo-8-oxa-3, 5-dithia-4-stannatetradecanoate | ≤0.3 | No. | No. | No. | Yes. | No. |

State regulations

Massachusetts : The following components are listed: METHYL ETHYL KETONE (MEK); ACETONE

New York : The following components are listed: Methyl ethyl ketone; 2-Butanone; Acetone; 2-Propanone

New Jersey : The following components are listed: METHYL ETHYL KETONE; 2-BUTANONE; ACETONE; 2-PROPANONE

Pennsylvania : The following components are listed: 2-BUTANONE; 2-PROPANONE

California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

| Ingredient name | Cancer | Reproductive | No significant risk level | Maximum acceptable dosage level |
|-----------------|--------|--------------|---------------------------|---------------------------------|
| Vinyl chloride | Yes. | No. | Yes. | - |
| Acetaldehyde | Yes. | No. | Yes. | - |

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Section 15. Regulatory information

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

[Inventory list](#)

| | |
|-----------------------------------|--|
| Australia | : All components are listed or exempted. |
| Canada | : All components are listed or exempted. |
| China | : All components are listed or exempted. |
| Europe | : All components are listed or exempted. |
| Japan | : Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined. |
| Malaysia | : Not determined. |
| New Zealand | : All components are listed or exempted. |
| Philippines | : All components are listed or exempted. |
| Republic of Korea | : All components are listed or exempted. |
| Taiwan | : Not determined. |
| Thailand | : Not determined. |
| Turkey | : Not determined. |
| United States | : All components are listed or exempted. |
| Viet Nam | : Not determined. |

Section 16. Other information

[Hazardous Material Information System \(U.S.A.\)](#)

| | | |
|------------------|---|---|
| Health | / | 2 |
| Flammability | | 3 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

[National Fire Protection Association \(U.S.A.\)](#)



Section 16. Other information

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

| Classification | Justification |
|--|---|
| FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 | On basis of test data Calculation method Calculation method Calculation method Calculation method |

History

Date of issue/Date of revision : 2/22/2018

Version : 1

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.