

# Technical Data Sheet



Eclectic Products LLC  
Manufacturing Facility  
101 Dixie Mae Drive  
Pineville, Louisiana  
eclecticproducts.com  
800.349.4667

ISO 9001:2008  
Compliant  
Quality Management  
Systems

Administration Office  
Eugene, Oregon  
eclecticproducts.com  
800.693.4667

## UNITED STATES



4 fl oz Bottle  
8 fl oz Bottle

*Not all styles/sizes/colors available in all areas.*



# UNICORN SPiT

## GEL STAIN AND GLAZE IN ONE!

### PRODUCT DESCRIPTION

**Unicorn SPiT** is a PAINT, GEL STAIN and GLAZE in One! The exquisite JASMINE SCENTED, VIBRANT COLORED stain is ideal for use in creating or refinishing tons of projects. It is available in 14 exquisite colors (4 fl oz/118.2 mL & 8 fl oz/236.5 mL sizes) that can be as opaque or vibrant as your dreams require. Use as a PAINT or dilute with water to create a GEL, STAIN, GLAZE, WHITE WASH or ANTIQUING TINT!

It stains deep into the bare wood grain or glazes over existing finishes, brightens and highlights chalk paint, and provides a three dimensional effect.

### WHERE TO USE / APPLICATIONS

UNICORN SPiT allows anyone to turn ordinary objects into personalized MASTERPIECES! Use on wood, glass, metal, fabric, pottery, wicker, concrete and laminate. Excellent for Crafters, Makers, Hobbyists, DIYers and Pros too!

### FEATURES AND BENEFITS

#### 14 VIBRANT COLORS

#### EXQUISITE JASMINE SCENT

**MULTIPLE PRODUCTS IN ONE** – Use as a PAINT or dilute with water to create a GEL, STAIN, GLAZE, WHITE WASH or ANTIQUING TINT!

**MULTI-SURFACE** – Can be used on almost any type of material.

**NON-TOXIC** – No harmful ingredients.

### TECHNICAL INFORMATION

PROPERTIES	
Color:	Various
Coverage:	4 fl oz (118.2 mL) = Up to a 38" x 19" area. 8 fl oz (236.5 mL) = Up to a 76" x 38" area.
Viscosity:	In pure form without dilution: 2300 Cp
Odor:	Jasmine scented
Solvents:	None
Dilutable:	Yes, dilute with <b>Water only</b> . See dilution chart on next page.
Drycleanable:	No. Do not dry clean.
Dry Time:	Approximately 30-60 minutes*
Service Temperature:	59 °F - 95 °F (15 °C – 35 °C)
Storage Temperature:	50 °F – 95 °F (10 °C – 35 °C)
Shelf life:	2 years

*\*Temperature and humidity may alter dry time.*

# Technical Data Sheet



## UNICORN SPiT

GEL STAIN AND GLAZE IN ONE!

### CANADA



118.2 mL Bottle

236.5 mL Bottle

*Not all styles/sizes/colors available in all areas.*

### EUROPE



118.2 mL Bottle

*Not all styles/sizes/colors available in all areas.*

### DIRECTIONS and APPLICATION NOTES

Use Unicorn SPiT as a paint, gel or stain on most any material. Create masterpieces on wood, glass, metal, fabric, pottery, concrete, laminate, wicker and most other substrates.

#### **GENERAL DIRECTIONS:**

SHAKE WELL and test small area before use. Can be applied with a brush, foam pad, or your hands! Dry time depends upon thickness of the application. Dry time is approximately 30-60 minutes (depending on material, humidity and temperature) or until a chalky finish appears. Unicorn SPiT dries quickly. Use a spray bottle of water to keep product from drying out and to easily manipulate. Once dry, use FAMOWOOD GLAZE COAT or other NON-WATER BASED coatings to protect add gloss and dimension.

**Laminate use:** Sand the surface with 220 sand paper after cleaning, then dust well before applying.

**Glass:** For best results, mix Unicorn SPiT with a WATER-BASED decoupage before applying to glass. For a solid/non-transparent color, use a 1:1 ratio of Unicorn SPiT /decoupage. For more transparent color (stained-glass style) results, use 1-part Unicorn SPiT to 4-parts decoupage. Apply mixture directly to glass and let cure completely. To add durability to the exterior of regularly handled items, spray a light, NON-WATER BASED clear coat over project and let dry.

#### **FABRIC USE**

- **Stamping method:** Use Unicorn SPiT full strength for “stamping” (creating design on a separate surface and then “stamping” it on to a fabric project). Then, use a water bottle and your hand or brush to blend.
- **Direct to fabric projects:** Mix Unicorn SPiT with 3-7 parts water in a spray bottle or cup and brush it on, drip it on or spray it on.
- **Protecting your finished project:** Use a NON-WATER BASED product intended for waterproofing fabric after Unicorn SPiT has completely dried.
- **Washing:** Unicorn SPiT will keep most of its color if treated before washing (see various methods below). Let dry for 24 hours before washing. For best results, wash in cold water by hand (with very little laundry detergent). Rinse with cold water. Various methods to increase the colorfastness of the Unicorn SPiT before washing are as follows:
  - **Fabric Medium:** Mix a Fabric Medium with Unicorn SPiT according to instructions on the Fabric Medium bottle.
  - **Allure® Dimensional Design Adhesive Paint:** Mix Unicorn SPiT with Allure Gloss (Shiny Clear) in a 1:1 ratio. Dry flat 5 hours. Washable after 72 hours.
  - **Non-water based fabric protectant:** Let Unicorn SPiT dry. Apply protectant. Allow to dry as indicated on product. Let set for 24 hours before washing.
  - **Hair Dryer:** Let Unicorn SPiT dry. Use hottest blow dryer setting to heat fabric until fabric is hot. Allow to cool back down to room temperature. Let set for 24 hours before washing.
  - **Iron:** Let Unicorn SPiT dry. Put iron on hottest setting (without moisture). Lay wax paper over fabric. Iron front and back of fabric until hot. Allow to cool back down to room temperature. Let set for 24 hours before washing.

# Technical Data Sheet



## UNICORN SPiT

### GEL STAIN AND GLAZE IN ONE!

#### MIDDLE EAST



118.2 mL Bottle

Not all styles/sizes/colors available in all areas.

#### AUSTRALIA/NZ



118.2 mL Bottle

236.5 mL Bottle

Not all styles/sizes/colors available in all areas.

- **Vinegar:** Put fabric with dried Unicorn SPiT design in cold water/vinegar at a 1:1 ratio mix. Let set in vinegar for 24 hours. Rinse with cold water and a very small amount of laundry detergent immediately after removing from water/vinegar solution. Lay flat to dry.
- **Clothes dryer:** Put fabric with dried Unicorn SPiT design in dryer for 1 hour on hottest setting. Remove and allow to cool to room temperature. Let set for 24 hours before washing.

\*Zia is not a colorfast color. Use other colors if project will be exposed to moisture.

NOTE: If a more washed-out look is desired: Let dry for 24 hours before washing. Machine wash in gentle cycle with cold water. Machine dry if desired.

#### Recommended dilution ranges:

Treatment / Application Type	Water Dilution Ratio
PAINT / HEAVY GLAZE or ANTIQUING / DRY BRUSHING	0-10%
LIGHT GLAZE / LIGHT WHITE-WASH / LIGHT ANTIQUING	10-30%
WOOD STAIN (BARE WOOD) / DYE FOR STAINED SURFACES	30-50%
DISTRESSED WOOD (BARE WOOD)	50-70%
FABRIC (Up to 85% water for spraying)	60-80%
CONCRETE	0-90%
GLASS	0-30%

NOTE: Distilled or purified water is recommended rather than hard or high mineral water.

#### DIRECTIONS FOR USE AS A PAINT, HEAVY GLAZE, or ANTIQUING/DRY BRUSHING ON WOOD, GLASS, METAL, FABRIC, POTTERY, WICKER, CONCRETE & LAMINATE:

- SHAKE BEFORE USING.
- Use Unicorn SPiT right out of the bottle for a paint application or dilute it up to 10% with water for antiquing or dry brushing. Diluting Unicorn SPiT with water allows you to control the opaqueness. For antiquing or dry brushing, add 10 parts Unicorn SPiT in a re-sealable container to be diluted with water. Test the dilution on a small, dry, clean sample piece of the same substrate as your project, gradually adding up to 1 part water until the desired effect is achieved.
- Apply the diluted Unicorn SPiT to the surface once it is completely void of all oil, sealer, dirt, grime, paint, stain, or anything that may inhibit the product from contacting the bare surface.
- Continue to add or blend multiple colors to the surface in separate areas creating designs to achieve the desired look.
- Allow to dry. Dry time is approximately 30-60 minutes (depending on material, humidity and temperature) or until a chalky finish appears.
- After drying, lightly buff the surface with a fine grain sand paper (120-220 grit) or extra-fine steel wool (following the grain) to remove any excess or clumps.
- Dust off thoroughly.
- Seal with FAMOWOOD GLAZE COAT or most any oil-based coating/sealer. For better protection and a higher gloss, repeat coats of sealer as indicated on the product's instructions. High gloss sealers will help achieve a three dimensional look.

**DIRECTIONS FOR USE AS A LIGHT GLAZE, WHITE WASH OR ANTIQUING AGENT:**

- SHAKE BEFORE USING.
- Dilute Unicorn SPiT up to 30% with water to make a light glaze, white wash or antiquing agent. Diluting Unicorn SPiT with water allows you to control the opaqueness. Add 10 parts Unicorn Spit in a re-sealable container to be diluted with water. Test the dilution on a small, dry, clean sample piece of the same substrate as your project, gradually adding up to 3 parts water until the desired effect is achieved.
- Apply the diluted Unicorn SPiT to the surface once it is completely void of all oil, dirt, grime, paint, stain, or anything that may inhibit the product from making contact with the surface to antique, age, paint, highlight or lowlight.
- Continue to add multiple colors to the surface in separate areas creating designs to achieve the desired look or blend colors as desired.
- Once dry, use a soft (dry or damp) cloth to polish away Unicorn SPiT until your desired effect has been achieved.
- Apply to unsealed chalk or mineral style paint to create custom color highlighting and lowlighting before sealing.
- Allow to dry. Dry time is approximately 30-60 minutes (depending on material, humidity and temperature) or until a chalky finish appears.
- Seal with FAMOWOOD GLAZE COAT or most any oil-based coating/sealer. For better protection and a higher gloss, repeat coats of sealer as indicated on the product's instructions. High Gloss Sealers will help achieve a three dimensional look.

**DIRECTIONS FOR USE AS A STAIN OR DYE:**

- SHAKE BEFORE USING.
- Dilute Unicorn SPiT up to 50% with water to make stain. Diluting Unicorn SPiT with water allows you to control the opaqueness and absorption into the porous surface. Add 10 parts Unicorn Spit in a re-sealable container to be diluted with water. Test the dilution on a small, dry, clean sample piece of the same substrate as your project, gradually adding up to 5 parts water until the desired effect is achieved.
- Apply the diluted Unicorn SPiT to the bare surface once it is completely void of all oil, sealer, dirt, grime, paint, stain, or anything that may inhibit the product from making contact with the bare porous surface.
- Continue to add or blend multiple colors to the surface in separate areas creating designs to achieve the desired look.
- Allow to dry. Dry time is approximately 30-60 minutes (depending on material, humidity and temperature) or until a chalky finish appears.
- After drying, lightly buff the surface with a fine grain sand paper (120-220 grit) or extra-fine steel wool (following the grain) to remove any excess or clumps.
- Dust off thoroughly.
- Seal with FAMOWOOD GLAZE COAT or most any oil-based coating/sealer. For better protection and a higher gloss, repeat coats of sealer as indicated on the product instructions. High Gloss Sealers will help achieve a three dimensional look.



---

## UNICORN SPiT

---

GEL STAIN AND GLAZE IN ONE!

---

**TIPS TO CREATE VARIOUS FINISHES:** Intermingle chalky paint finishes or metallic spray paint with Unicorn SPiT to achieve unique finishes. Top coats or finishes must be oil-based. Water-based coatings will alter the look of Unicorn SPiT.

**CUSTOM COLORS:** Most water-based paints (chalk style or mineral based) can be mixed with Unicorn SPiT® to create custom colors.

---

### HEALTH and SAFETY

---

Before working with this product, read and become familiar with information concerning hazards, proper use and handling. SDS's are available online at the following links:

United States-

English: <http://eclecticproducts.com/downloads/sds-ucspit-english.pdf>

Spanish: [http://eclecticproducts.com/downloads/sds-ucspit-spanish\\_us.pdf](http://eclecticproducts.com/downloads/sds-ucspit-spanish_us.pdf)

Canada-

English: <http://eclecticproducts.com/downloads/sds-ucspit-english.pdf>

French: <http://eclecticproducts.com/downloads/sds-ucspit-canada.pdf>

Europe-

English (Request SDS): [sds@eclecticproducts.com](mailto:sds@eclecticproducts.com)

French (Request SDS): [sds@eclecticproducts.com](mailto:sds@eclecticproducts.com)

German (Request SDS): [sds@eclecticproducts.com](mailto:sds@eclecticproducts.com)

Spanish (Request SDS): [sds@eclecticproducts.com](mailto:sds@eclecticproducts.com)

Middle East-

Arabic & English (Request SDS): [sds@eclecticproducts.com](mailto:sds@eclecticproducts.com)

Australia/New Zealand-

English (Request SDS): [sds@eclecticproducts.com](mailto:sds@eclecticproducts.com)

To request a hard copy of the SDS, please send an e-mail to [sds@eclecticproducts.com](mailto:sds@eclecticproducts.com).

---

### LIMITED WARRANTY

---

The product is warranted against any defect in materials or workmanship under normal use for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc., P.O. Box 4450, Pineville LA 71361 or call 800.767.4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.