

Data Sheet



Eclectic Products LLC Manufacturing Facility 101 Dixie Mae Drive Pineville, Louisiana eclecticproducts.com 800-349-4667

Customer Service 1-800-349-4667

Technical Support 1-800-767-4667

Administration Office Eugene, Oregon eclecticproducts.com 800-693-4667

ISO 9001:2015 Compliant **Quality Management** Systems



UNITED STATES / MEXICO



4.0 fl oz/118.2 mL Bottle (6 colors)

UNICORN SPIT METALLIC

PAINT, GEL STAIN AND GLAZE

PRODUCT DESCRIPTION

Unicorn SPit VIBRANT COLORED METALLIC gel stains allow you to easily create unparalleled, rich, luminous finishes on furniture, home décor, fabric and craft projects. Iridescent mica interacts with light to maximize the shimmer and sheen of the finish. The highly concentrated formulas enable you to create what your imagination dreams, so get inspired!

WHERE TO USE / APPLICATIONS

Turn ordinary objects and projects into personalized MASTERPIECES! Use it on bare wood or over existing finishes as a glaze. Excellent for Crafters, Makers, Hobbyists, DIYers and Pros too! Use on:

- Wood •
- Fabric •
- Glass •
- Stone
- Ceramic
- Metal
- Wicker •
- Concrete .
- Laminate & more!

FEATURES AND BENEFITS

6 VIBRANT METALLIC COLORS -- Mercury (Silver), Zeus (Gold), Hephaestus (Bronze), Aphrodite (Rose Gold), Poseidon (Patina), Athena (Copper) **REFRESHING GREEN TEA SCENT** MULTIPLE PRODUCTS IN ONE - Use over existing finishes as a PAINT, GEL STAIN, or LUMINOUS GLAZE! WATER-BASED, EASY CLEAN-UP MULTI-SURFACE - Can be used on almost any type of material. NON-TOXIC **CONCENTRATED** COAT WITH FAMOWOOD GLAZE COAT FOR A DEEP 3-D FINISH

TECHNICAL INFORMATION

PHYSICAL & PERFORMANCE PROPERTIES				
COLOR:	Various			
APPROX. COVERAGE	Film Thickness	1 mil	2 mil	3 mil
	4.0 fl oz/118.2 mL	50 ft ²	25 ft ²	12.5 ft ²
TECHNOLOGY:	Waterbased			
VOC:	<3% by weight			
VISCOSITY:	Undiluted: 2,800 to 3,400 cP (at 76 °F -78 °F)			
DRY TIME*:	Approx. 30-60 minutes			
APPLICATION TEMP:	Ideal application temperature range is 55 °F to 95 °F (13 °C to 35 °C).			
SERVICE TEMP:	55 °F to 95 °F (13 °C to 35 °C)			
DILUTABLE:	Yes, product for immediate use may be diluted with water (up to 5 parts water until			
	the desired effect is achieved). Do not dilute product to be stored for later use.			
ODOR:	Green Tea scented			
STORAGE:	Store out of direct light between 50 °F and 95 °F (10 °C and 35 °C).			
CLEAN-UP:	Clean up with soap/water			
FREEZE/THAW STABILITY:	It is recommended to keep the product from freezing whenever possible. If the product			
	should freeze, it is stable and re-workable up to three freeze cycles.			
SHELF LIFE:	1.5 years.			
*Depending on surface material, film thickness, humidity and temperature.				

Technical Data Sheet



118.2 mL Bottle (6 colors)



118.2 mL Bottle (6 colors)

AUSTRALIA/ NEW ZEALAND



118.2 mL Bottle (6 colors)

UNICORN SPIT METALLIC

DIRECTIONS AND APPLICATION NOTES

GENERAL DIRECTIONS:

SHAKE WELL BEFORE USING.

- 1. Test small area before use.
- 2. Apply with a natural fiber or synthetic brush and let dry! Foam brushes not recommended.
- Dry time depends upon thickness of the application. Dry time is approximately 30-60 minutes (depending on material, humidity and temperature). If you are working on a project and the stain is a little dry to work with, spray lightly with water to continue manipulating the product.
- 4. Apply additional layers until desired effect is achieved. The more layers, the more shimmering and vibrant your project will be!
- Once dry, use FAMOWOOD GLAZE COAT or other <u>NON-WATER-BASED</u> coatings to protect, add gloss and dimension. For outdoor projects, make sure to protect your masterpiece with oil-based finishes or coatings that indicate they are adequate for outdoor use.

DILUTION: Product may be diluted before use to achieve a more translucent or gel stain effect (only dilute the amount of Unicorn SPiT METALLIC intended for immediate use). Diluting Unicorn SPiT METALLIC will reduce the shimmer—so it is recommended to test the dilution on a small, dry, clean sample piece of the same substrate as your project, gradually adding up to 5 parts water until the desired effect is achieved.

GLASS OR OTHER NON-POROUS SURFACES (THAT CANNOT BE SANDED):

- 1. Applications that do not require brushing: Pour undiluted product directly on the substrate.
- 2. Applications that require using a brush or to provide some water resistance:
 - <u>OPTION #1</u>. Mix 2 part Unicorn SPiT / 1 part Fabri-Fuse, paint additive (ex., Floetrol) or dishwasher safe decoupage and apply.
 - <u>OPTION #2</u>. Apply a paint additive or E6000 Fabri-Fuse as a primer directly to your project and let cure completely. Then, apply Unicorn SPiT METALLiC over the cured paint additive or E6000 Fabri-Fuse.

LAMINATE OR OTHER NON-POROUS SURFACES (THAT CAN BE SANDED): Sand the surface with 220 sand paper after cleaning, then dust well before applying. Because Unicorn SPiT is translucent, a primer coat may be required for best results. Paint the laminate (before applying Unicorn SPiT) with a water-based primer. Once dry, use FAMOWOOD GLAZE COAT or other <u>NON-WATER-BASED</u> coatings to protect, add gloss and dimension.

POLYMER CLAY APPLICATIONS:

- 1. Bake polymer clay per manufacturer's directions.
- 2. Allow clay to completely cool.
- 3. Apply a white base coat of Unicorn SPiT directly onto the baked polymer clay with a fine-tip paint brush. Let dry and then apply Unicorn SPiT METALLIC.
- 4. Allow to dry (approx. 30-60 minutes).
- 5. Reapply as desired.

UNICORN SPIT METALLIC

Technical Data Sheet

FABRIC USE:

- Stamping method: Use Unicorn SPiT METALLIC at full strength for block printing or "stamping" (creating design on a separate surface and then "stamping" it on to a fabric project). Unicorn SPiT METALLIC can be applied to your stamp using a brayer or by dabbing a sponge stencil brush. Then, use a water bottle and your hand or brush to blend if desired.
- Direct to fabric projects: Use full strength or mix with 1-5 parts water in a spray bottle or cup and brush, drip or spray it on. If diluted, it is recommended to test the dilution on a small, dry, clean sample piece of the same substrate as your project, gradually adding up to 5 parts water until the desired effect is achieved.
- Washing: Unicorn SPiT will keep most of its color if treated before washing (see various methods

below). Wash in cold water by hand (use very little laundry detergent). Rinse with cold water. Machine washing is not recommended.

FOR MORE PERMANENT RESULTS:

- E6000 Fabri-Fuse: Mix Unicorn SPiT with up to equal parts of E6000 Fabri-Fuse. Dry flat for 5 hours. Washable after 72 hours. *This WILL change the texture, durability and feel of the fabric.
- Fabric Medium: Mix a Fabric Medium with Unicorn SPiT according to instructions on the Fabric Medium bottle.
- Non-water based fabric protectant: Let Unicorn SPiT dry. Apply protectant. Allow to dry as indicated on product. Let set for 24 hours before washing.

FOR SEMI-PERMANENT RESULTS:

- Hair Dryer: Let Unicorn SPiT dry. Use hottest blow dryer setting to heat fabric until fabric is hot. Allow fabric to cool back down to room temperature. Let set for 24 hours before washing.
- Iron: Let Unicorn SPiT dry. Put iron on hottest setting (without moisture). Lay wax paper over fabric. Iron front and back of fabric until hot. Allow to cool back down to room temperature. Let set for 24 hours before washing.
- Vinegar: Put fabric with dried Unicorn SPiT in cold water/vinegar mixed at a 1:1 ratio. Let fabric set in vinegar/water mix for 24 hours. Rinse with cold water and a very small amount of laundry detergent immediately after removing from water/vinegar solution. Lay flat to dry.
- Clothes dryer: Put fabric with dried Unicorn SPiT in dryer for 1 hour on hottest setting. Remove and allow fabric to cool to room temperature. Let set for 24 hours before washing.

NOTE: Distilled or purified water is recommended rather than hard or high mineral water.

MIXING COLORS: Mix Unicorn SPIT METALLIC colors together to create your own special color OR mix most any water-based paint (chalk style or mineral based) with Unicorn SPIT METALLIC to create custom colors.

TINTING FAMOWOOD GLAZE COAT EPOXY RESIN WITH UNICORN SPIT

Use Unicorn SPiT METALLiC as a tinting agent to add brilliant color, shimmer and sparkle to epoxy projects. Famowood Glaze Coat High Gloss Finish or Famowood Glaze Coat High Gloss Craft Resin is recommended. For all other brands, test before use.

DIRECTIONS:

- 1. Measure and mix Famowood Glaze Coat as directed.
- 2. Quickly add drops of undiluted Unicorn SPiT (Original, SPARKLiNG or METALLiC) to achieve your desired color. DO NOT use more than 1 part Unicorn SPiT to 5 parts epoxy. Remember...A tiny bit of Unicorn SPiT goes a long way.
- 3. If multiple colors are desired, gather smaller containers to work with in advance. Then measure, mix and pour Glaze Coat epoxy immediately into smaller containers and add Unicorn SPiT.
- 4. Pour tinted epoxy onto your project and finish your masterpiece!
- 5. Follow epoxy pouring, curing and clean-up instructions.

HEALTH & SAFEEY

Before working with this product, read and become familiar with information concerning hazards, proper use and handling. To request a Safety Data Sheet, please send an email to <u>sds@eclecticproducts.com</u>.

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. The manufacturer will not accept liability for more than product replacement. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products LLC, P.O. Box 4450, Pineville, LA 71361 or call 1-800-767-4667. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. This warranty gives you specific legal rights, and you also have other rights, which vary from province to province.